

JMP-90

 **alliance**



GENERAL

RADIO REMOTE **Wireless Transmitter System/w Tethered Backup Remote**

VIBRATOR **Standard**

WATER TANK **750 L (198 G)**

WATER PUMP **Hydraulic Power 20 bar (290 psi)**

WEAR PARTS **Carbide**

OUTRIGGER **Hydraulic Rear**

TOOL BOX **Standard**

WEIGHT **23,635 lbs /10,720 kg (Model As Shown)**

POPULAR UPGRADES[†]

- Air Chuck
- Additional Tool Box
- Storage Rack
- Under Deck Lighting
- Heated Water Tank
- Heated Hydraulic Tank

PUMP

OUTPUT: **Rod Side 90 m³/h (118 yd³/h)**

Piston Side 60 m³/h (78 yd³/h)

PRESSURE: **Rod Side 71 bar (1030 psi)**

Piston Side 106 bar (1536 psi) ‡

STROKES PER MINUTE **Rod Side 32**

Piston Side 22

HARD CHROMED CONCRETE CYLINDER **200 mm x 1400 mm (8" X 55")**

S-TUBE SIZE **200 mm x 178 mm (8" x 7")**

OUTLET **152 mm (6" ZX)**

MAX. AGGREGATE SIZE **63 mm | 2.5"**

HYDRAULIC PUMP **All Hydraulic Switching System A11V0145**

HYDRAULIC SYSTEM PRESSURE **350 bar (5076 PSI)**

SWITCHING SYSTEM **Hydraulic w/Manual Override**

LUBE SYSTEM (HOPPER) **Lincoln Automatic Greaser**

HOPPER CAPACITY **21.1 cubic ft (600 L) Easy Clean**

OUTRIGGER LOAD **50 KN | 11,250 LBS**

[†]More options available, ask your sales rep for details.
Alliance Concrete Pumps Inc. reserves
the right to make changes to all specifications

allianceconcretepumps.com

 **CANADIAN HEAD OFFICE**
1.888.870.0908

 **EAST COAST BRANCH**
1.888.584.7231

 **TEXAS BRANCH**
1.817.442.6420