

JFS-12 HP

alliance



GENERAL

RADIO REMOTE **Wireless Transmitter System/w Tethered Backup Remote**

VIBRATOR **Standard**

WATER TANK **750 L (198 G)**

WATER PUMP **Hydraulic Power 20 bar (290 psi)**

WEAR PARTS **Carbide**

OUTRIGGER **Hydraulic Front & Rear**

TOOL BOX **Standard**

WEIGHT **31,660 lbs/14,360 kg (Model As Shown)**

POPULAR UPGRADES[†]

- Air Chuck
- Additional Tool Box
- Storage Rack
- Under Deck Lighting
- Heated Water Tank
- Heated Hydraulic Tank

PUMP

OUTPUT:

Rod Side	115 m³/h (150 yd³/h)
Piston Side	72 m³/h (94 yd³/h)

PRESSURE:

Rod Side	92 Bar (1334 psi) [†]
Piston Side	148 bar (2146 psi) [†]

STROKES PER MINUTE

Rod Side	30
Piston Side	19

HARD CHROMED CONCRETE CYLINDER **200 mm x 2100 mm (8" X 83")**

S-TUBE SIZE **200 mm x 178 mm (8" x 7")**

OUTLET **152 mm (6" ZX)**

MAX. AGGREGATE SIZE **63 mm | 2.5"**

HYDRAULIC PUMP **Rexroth Hydromatic A11VL0260**

HYDRAULIC SYSTEM PRESSURE **350 bar (5076 PSI)**

SWITCHING SYSTEM **Hydraulic w/Manual Override**

LUBE SYSTEM (HOPPER) **Lincoln Automatic Greaser**

HOPPER CAPACITY **21.1 cubic ft (600 L) Harsh Mix Hopper**

OUTRIGGER LOAD **50 KN | 11,250 LBS**

[†]More options available, ask your sales rep for details.
Alliance Concrete Pumps Inc. reserves
the right to make changes to all specifications

allianceconcretepumps.com

 **CANADIAN HEAD OFFICE**
1.888.870.0908

 **EAST COAST BRANCH**
1.888.584.7231

 **TEXAS BRANCH**
1.817.442.6420