

JSP-2110 HP

 **alliance**



GENERAL

RADIO REMOTE	Wireless Transmitter System/w Tethered Backup Remote
VIBRATOR	Standard
WATER PUMP	Hydraulic Power 20 bar (290 psi)
WEAR PARTS	Carbide
ENGINE	450hp Cummins Diesel
OUTRIGGER	Hydraulic Front/ Manual Rear
WEIGHT	18,298 lb 8,300 kg
OPTIONS	Road Legal (Street Legal Towing Package)

PUMP

OUTPUT:	Rod Side	100 m ³ /h (130 yd ³ /h)
	Piston Side	68 m ³ /h (89 yd ³ /h)
PRESSURE:	Rod Side	153 bar (2,219 psi)
	Piston Side	224 bar (3,248 psi) ‡
STROKES PER MINUTE	Rod Side	25
	Piston Side	17
HARD CHROMED CONCRETE CYLINDER		200 mm x 2100 mm (8" x 83")
S-TUBE SIZE		200 mm x 152 mm (8" x 6")
OUTLET		152 mm (6" HD)
MAX. AGGREGATE SIZE		63 mm 2.5"
HYDRAULIC PUMP		Kawaski Twin K3V180
HYDRAULIC SYSTEM PRESSURE		350 bar (5076 PSI)
SWITCHING SYSTEM		Electric w/Manual Override
LUBE SYSTEM (HOPPER)		Lincoln Automatic Greaser
HOPPER CAPACITY		21.1 cubic ft (600 L) Harsh-Mix Reinforced Hopper

‡ More options available, ask your sales rep for details.
Alliance Concrete Pumps Inc. reserves
the right to make changes to all specifications

allianceconcretepumps.com

 **CANADIAN HEAD OFFICE**
1.888.870.0908

 **EAST COAST BRANCH**
1.888.584.7231

 **TEXAS BRANCH**
1.817.442.6420