

JM-2100 HP

 **alliance**



GENERAL

RADIO REMOTE **Wireless Transmitter System/w Tethered Backup Remote**

VIBRATOR **Standard**

WATER TANK **1000 L (264 G)**

WATER PUMP **Hydraulic Power 20 bar (290 psi)**

WEAR PARTS **Carbide**

OUTRIGGER **Hydraulic Front & Rear**

TOOL BOX **Standard**

WEIGHT **38,580 lbs /17,500Kg (Model As Shown)**

POPULAR UPGRADES[†]

- Air Chuck
- Additional Tool Box
- Storage Rack
- Under Deck Lighting
- Heated Water Tank
- Heated Hydraulic Tank

PUMP

OUTPUT:

Rod Side	100 m³/h (131 yd³/h)
Piston Side	70 m³/h (92 yd³/h)

PRESSURE:

Rod Side	153 bar (2218 psi) ‡
Piston Side	224 bar (3248 psi) ‡

STROKES PER MINUTE

Rod Side	25
Piston Side	17

HARD CHROMED CONCRETE CYLINDER **200 mm x 2100 mm (8" X 83")**

S-TUBE SIZE **200 mm x 152 mm (8" x 6")**

OUTLET **152 mm (6" ZX)**

MAX. AGGREGATE SIZE **63 mm | 2.5"**

HYDRAULIC PUMP **Rexroth Hydromatic A20V0190**

HYDRAULIC SYSTEM PRESSURE **350 bar (5076 PSI)**

SWITCHING SYSTEM **Electric w/Manual Override**

LUBE SYSTEM (HOPPER) **Lincoln Automatic Greaser**

HOPPER CAPACITY **21.1 cubic ft (600 L) Harsh Mix Reinforced Hopper**

OUTRIGGER LOAD **50 KN | 11,250 LBS**

[†]More options available, ask your sales rep for details.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications

allianceconcretepumps.com

 **CANADIAN HEAD OFFICE**
1.888.870.0908

 **EAST COAST BRANCH**
1.888.584.7231

 **TEXAS BRANCH**
1.817.442.6420